



EXCELLIUM SM 5W50

Premium Fully Synthetic multigrade oil for passenger car engine

APPLICATIONS

Gasoline / diesel engine cars

- A premium fully synthetic engine oil with special protective additives for ultimate level of engine protection that exceeds USA and European industry standards.
- Recommended for all petrol engines (multi-valve and turbo types, with or without catalytic converter) and all diesel engines, turbo-charged or naturally aspirated in cars and light vans.

Arduous service conditions

- Designed to provide protection under severe driving style or conditions.
- Stability and endurance under extreme conditions (heat, load, speed) that can cause conventional oils to break down.

PERFORMANCES

International specifications

- API SM/CF (API Donut)
- ACEA A3/B3

Recommended for use

- Ford, GM, PSA, BMW, VW, Audi and Mercedes-Benz

CUSTOMER BENEFITS

Optimised performance

- Ensures excellent engine cleanliness and wear protection for vehicles in city and suburban driving conditions.

Lengthens engine life

- Excellent thermal and oxidation stability.
- An unique combination of advanced synthetic and meticulously selected additives provide freedom of ring sticking, reduction in deposits leading to a reduced engine wear and to a longer engine and component life.

Low temperature flow properties
Compatibility with a wide range of seal materials

- Thanks to its fully synthetic formulation, has an exceptional viscosity index.
- Circulates rapidly within the engine to minimize cold start up wear. Improves low temperature engine efficiency over conventional mineral oil.
- Ensures the important engine seals stay soft and pliable to minimize oil leakage.

CHARACTERISTICS

Elf Excellium SM	Method	Units	SAE 5W50
Volumetric mass at 15°C	ASTM D1298	kg/m ³	853
Viscosity at 40°C	ASTM D445	mm ² /s	114
Viscosity at 100°C	ASTM D445	mm ² /s	18.36
Viscosity Index	ASTM D2270	-	180
Pour Point	ASTM D97	°C	-39
Flash Point	ASTM D92	°C	230

The typical characteristics mentioned represent mean values

Elf Excellium SM 5W50
Version May, 2005

This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard.
A safety data file conforming to the requirements of current E.U. legislation is available from your local trade consultant.